



Features

- Ultra-low Q_G For High Efficiency
- Logic Level
- Light Weight – 0.170 grams
- New Compact Hermetic Package with Dual Gate
- Source Sense Pin
- Total Dose
 - Rated to 1000 krad
- Single Event
 - SEE immunity for LET of 85 MeV/mg/cm² with V_{DS} up to 100% of rated Breakdown
- Low Dose Rate at 100 mRad/sec
 - Maintains Pre-Rad specification
- Neutron
 - Maintains Pre-Rad specification for up to 3×10^{15} Neutrons/cm²



EPC7018G

**Rad Hard eGaN® 100 V, 80 A,
6.0 mΩ Surface Mount**

Description

EPC Space FSMD-G series of eGaN® power switching HEMTs have been specifically designed for critical applications in the high reliability or commercial satellite space environments. These devices have exceptionally high electron mobility and a low temperature coefficient resulting in very low $R_{DS(on)}$ values. The lateral structure of the die provides for very low gate charge (Q_G) and extremely fast switching times. These features enable faster power supply switching frequencies resulting in higher power densities, higher efficiencies and more compact packaging.

Applications



- Satellite and Avionics
- Deep Space Probes
- High Speed Rad Hard DC-DC Conversion
- Rad Hard Motor Controllers
- Nuclear Facilities

Thermal Characteristics

Symbol	Parameter-Conditions	Value	Units
$R_{\theta JA}$	Thermal Resistance Junction to Ambient (Note 3)	48	°C/W
$R_{\theta JC}$	Thermal Resistance Junction to Case	1.53	

I/O Pin Assignment (Bottom View)

Pin	Symbol	Description
1	G	Gate
2	G	Gate
3	D	Drain
4	S	Source
5	SS	Source Sense



Absolute Maximum Rating ($T_C = 25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter-Conditions	Value	Units
V_{DS}	Drain to Source Voltage (Note 1)	100	V
	Drain-to-Source Voltage (up to 10,000 5 ms pulses at 150°C)	120	
I_D	Continuous Drain Current I_D @ $V_{GS} = 5\text{ V}$	80	A
I_{DM}	Single-Pulse Drain Current $t_{pulse} = 300\text{ }\mu\text{s}$	345	
V_{GS}	Gate to Source Voltage (Note 2)	+6 / -4	V
T_J, T_{STG}	Operating and Storage Junction Temperature Range	-55 to +150	°C
T_{SOL}	Package Mounting Surface Temperature	260	
ESD	ESD Class	ΔB	

Static Characteristics (*Typical (TYP) values are for reference only.*)

Parameter	Symbol	Test Conditions	MIN	TYP	MAX	Units
Drain to Source Voltage	$B_{V_{DS}}$	$V_{GS} = 0\text{ V}, I_D = 0.9\text{ mA}$	100			V
Drain to Source Leakage	I_{DSS}	$V_{DS} = 100\text{ V}, V_{GS} = 0\text{ V}$	$T_C = 25^\circ\text{C}$	0.001	0.4	mA
		$V_{DS} = 100\text{ V}, V_{GS} = 0\text{ V}$	$T_C = 125^\circ\text{C}$	0.01		
Gate to Source Forward Leakage	I_{GSS}	$V_{GS} = 5\text{ V}$	$T_C = 25^\circ\text{C}$	0.01	0.5	
Gate to Source Forward Leakage [#]		$V_{GS} = 5\text{ V}$	$T_C = 125^\circ\text{C}$	0.05		
Gate to Source Reverse Leakage		$V_{GS} = -4\text{ V}$	$T_C = 25^\circ\text{C}$	0.01	0.5	
Gate to Source Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 12\text{ mA}$	$T_C = 25^\circ\text{C}$	0.8	1.2	V
Gate to Source Threshold Voltage Temperature Coefficient	$\Delta V_{GS(th)}$		$-55^\circ\text{C} < T_A < 150^\circ\text{C}$	-1.9		mV/°C
Drain to Source Resistance (Note 4)	$R_{DS(on)}$	$V_{GS} = 5\text{ V}, I_D = 40\text{ A}$	$T_C = 25^\circ\text{C}$	5.2	6.0	mΩ
Source to Drain Forward Voltage (Note 5)	V_{SD}	$I_S = 0.5\text{ A}, V_G = 0\text{ V}$	$T_C = 25^\circ\text{C}$	1.8		V

All measurements were done with substrate shorted to source.

Defined by design. Not subject to production test.

Dynamic Characteristics ($T_C = 25^\circ\text{C}$ unless otherwise noted. *Typical (TYP) values are for reference only.*)

Parameter	Symbol	Test Conditions	MIN	TYP	MAX	Units
Input Capacitance	C_{ISS}	$V_{DS} = 50\text{ V}, V_{GS} = 0\text{ V}$		1240		pF
Reverse transfer Capacitance	C_{RSS}			5.7		
Output Capacitance	C_{OSS}			740		
Effective Output Capacitance, Energy Related	$C_{OSS(ER)}$	$V_{DS} = 0\text{ to }50\text{ V}, V_{GS} = 0\text{ V}$		970		
Effective Output Capacitance, Time Related	$C_{OSS(TR)}$			1250		
Total Gate Charge	Q_G	$V_{DS} = 50\text{ V}, V_{GS} = 5\text{ V}, I_D = 40\text{ A}$		11.7		nC
Gate to Source Charge	Q_{GS}	$V_{DS} = 50\text{ V}, I_D = 40\text{ A}$		4.0		
Gate to Drain Charge	Q_{GD}			2.1		
Output Charge (Note 6)	Q_{OSS}	$V_{DS} = 50\text{ V}, V_{GS} = 0\text{ V}$		63		
Source to Drain Recovery Charge	Q_{RR}			0		

All measurements were done with substrate shorted to source.

Radiation Characteristics

EPC Space eGaN® HEMTs are tested according to MIL-STD-750 Method 1019 for total ionizing dose validation. Every manufacturing lot is tested for total ionizing dose of Gamma radiation with an in-situ bias for (i) $V_{GS} = 5\text{ V}$, (ii) $V_{DS} = V_{GS} = 0\text{ V}$ and (iii) $V_{DS} = 80\% B_{VDSS}$.

Electrical Characteristics up to 1000 krad ($T_C = 25^\circ\text{C}$ unless otherwise noted. Typical (TYP) values are for reference only.)

Parameter	Symbol	Test Conditions	MIN	TYP	MAX	Units
Maximum Drain to Source Voltage	V_{DSMAX}	$V_{GS} = 0\text{ V}$, $I_D = 0.9\text{ mA}$	100			V
Gate to Source Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}$, $I_D = 12\text{ mA}$	0.8	1.2	2.5	
Drain to Source Leakage	I_{DSS}	$V_{DS} = 100\text{ V}$, $V_{GS} = 0\text{ V}$		0.001	0.4	mA
Gate to Source Forward Leakage	I_{GSS}	$V_{GS} = 5\text{ V}$		0.01	0.5	
Gate to Source Reverse Leakage		$V_{GS} = -4\text{ V}$		0.01	0.5	
Drain to Source Resistance (Note 4)	$R_{DS(on)}$	$I_D = 40\text{ A}$, $V_{GS} = 5\text{ V}$		5.2	6.0	mΩ

Typical Single Event Effect Safe Operating Area

Note : All Single Event Effect testing is performed on the K-500 Cyclotron at Texas A&M University

Test		Environment			V_{DS} Voltage (V)	
See SOA	Ion	LET MeV/mg/cm ²	Range μm	Energy MeV	$V_{GS} = 0\text{ V}$	$V_{GS} = -4\text{ V}$
	Xe	50	131	1653	100	100
	Au	83.7	130	2482	100	100




Figure 1: Typical Single Event Effect Safe Operating Area

Figure 2: Typical Output Characteristics at 25°C




Figure 3: Typical Output Characteristics at 125°C




Figure 4: Typical Transfer Characteristics




Figure 5: $R_{DS(on)}$ vs. V_{GS} for Various TemperaturesFigure 6: $R_{DS(on)}$ vs. V_{GS} for Various Drain Currents

Figure 7: Normalized Threshold Voltage vs. Temperature




Figure 8: Normalized On-State Resistance vs. Temperature




Figure 9: Typical Capacitance (Linear Scale)







Figure 10: Typical Gate Charge

Figure 11: Typical Output Charge and C_{OSS} Stored Energy


Package
Outline and
Dimensions



Symbol	Inches		Millimeters		Note
	MIN	MAX	MIN	MAX	
A (2x)	0.028	0.038	0.711	0.965	
B (3x)	0.075	0.085	1.905	2.159	
C (3x)	0.025	0.035	0.635	0.889	
D	0.015	0.025	0.381	0.635	
E	0.051	0.061	1.295	1.549	
F	0.024	0.034	0.61	0.864	
G	0.07	0.08	1.778	2.032	
H	0.078	0.088	1.981	2.235	
J	0.215	0.225	5.461	5.715	
K	0.311	0.321	7.899	8.153	

Standard Terminal Pad finish is a solder alloy of 63%Pb 37%Sn


Package Connections



Notes

- Note 1. NEVER exceed the absolute maximum V_{DS} of the device otherwise permanent damage/destruction may result.
- Note 2. NEVER exceed the absolute maximum V_{GS} of the device otherwise permanent damage/destruction may result. We recommend use at no greater than +5 V as the HEMT is fully conducting at this point.
- Note 3. $R_{\theta JA}$ measured with LCC3 package mounted to double-sided PCB, 0.063" thickness with 1.0 square inches of copper area on the top (mounting side) and a flood etch (3 square inches) on the bottom side.
- Note 4. Measured using four wire (Kelvin) sensing and pulse measurement techniques. Measurement pulse width is 80 μs and duty cycle is 1%, maximum.
- Note 5. With pulse measurement width 100–380 μs .
- Note 6. Guaranteed by design/device construction. Not tested.

EPC Space Part Number Information



Ordering Information Availability

Screening Options	Rad Assurance Options
1 character	1 character
C = Developmental Unit S = Space Level ¹ K = Die Space Level Screen	H = 1000 krad LET = 84

Part Number	Screening Level	Shipping Media
EPC7018GC	Developmental Units	Waffle Trays Tape and Reel
EPC7018GSH	Space Level	
EPC7018KH	Die Space Level	

¹ Screening and qualification consistent to an equivalent MIL-PRF-19500 specification.

EPC7018GC and EPC7018C devices are intended for engineering development purposes only and are NOT intended to be used as flight units.

EPC Space Rad Hard HEMT are not sensitive to Total Ionizing Dose as such the H level covers the R,F,G radiation levels.

Screening Flow Equivalent to a MIL-PRF-19500 General Specification

EPC SPACE Qual Flow Equivalent to a MIL-PRF-19500 Specification					
Operation	Test	Test Methods Per Mil STD 750	Sample Size	Space Level	COT
Pre-Assembly	Probe Testing	EPC SPACE Internal	100%	✓	✓
	Visual inspection	EPC SPACE Internal	100%	✓	✓
Post-Assembly	Die Shear	2,017	5	✓	✓
	X-Ray	2076	5	✓	✓
Screening	Serilialization		100%	✓	
	Electricals	3411,3413,3421,3404	100%	✓	✓
	Temp Cycling	1051	100%	✓	
	Constant Acceleration	2006	100%	✓	
	PIND	2052	100%	✓	
	Initial Electricals (Read and Record)	3411,3413,3421,3404	100%	✓	
	HTGB	1042 Condition B	100%	✓	
	Interim Electricals (Read and Record)	3411,3413,3421,3404	100%	✓	
	HTRB	1042 Condition A 240 Hours	100%	✓	
	Final Electricals (Read and Record)	3411,3413,3421,3404	100%	✓	
	Final Electricals (High and Low Temperatures)	3411,3413,3421,3404	100%	✓	
	Deltas	Per Procurement Specification	100%	✓	
	Percent Defective Allowable	Per Procurement Specification	100%	✓	
	Dynamic RDSON	EPC SPACE Internal	100%	✓	
	OutLiers Removal	EPC SPACE Internal	100%	✓	
	X-RAY	2076	100%	✓	
	Tinning		100%	✓	
	Hermetic Seal, Fine & Gross Leak	1071	100%	✓	
	Final Electricals	3411,3413,3421,3404	100%	✓	
Group A Inspection (Conformance)	A-2 DC Static Tests at 25°C	3411,3413,3421,3404	116	✓	
	A-3 High & Low Temp DC Static Tests	3411,3413,3421,3404	116	✓	
	A-7 Gate Charges	3471 Condition B	45	✓	
	A-7 Capacitance	3473	45	✓	
Group B Inspection (Conformance)	B-1, B-2, B-3, B-4, B-5	Sample base equivalent to a MIL-PRF-19500 flow or as required by procurement speciffication			
Group C Inspection (Conformance)	C-1, C-2, C-3, C-4, C-6, C-7	Sample base performed yearly per package style equivalent to a MIL-PRF-19500 flow or as required by procurement specification			
Group D Inspection (Conformance)	TID	1019	15	✓	
	SEE	1080	5	✓	
Group E Inspection (Qualification Inspection)	E-1, E-2, E-5, E-6 E-7	Performed during product introduction or a major process change equivalent to a MIL-PRF-19500 flow or as required by procurement specification			
	E8 Switching				

Disclaimers

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE. EPC Space Corporation, its affiliates, agents, employees, and all persons acting on its or their behalf (collectively, "EPC Space"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product. EPC Space makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose. To the maximum extent permitted by applicable law, EPC Space disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability. Statements regarding the suitability of products for certain types of applications are based on EPC Space market knowledge of typical requirements that are often placed on similar technologies in generic applications. Product specifications do not expand or otherwise modify EPC Space terms and conditions of purchase, including but not limited to the warranty expressed therein. Except as expressly indicated in writing, EPC Space products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the EPC Space product could result in personal injury or death. Customers using EPC Space products not expressly indicated for use in such applications do so at their own risk. Please contact authorized EPC Space personnel to obtain written terms and conditions regarding products designed for such applications. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of EPC Space. Product names and markings noted herein may be trademarks of their respective owners.

Export Administration Regulations (EAR)

The products described in this datasheet are subject to the U.S. Export Administration Regulations (EAR), 15 C.F.R. Pts 730-774, and are classified in ECCN 9A515.e. These products may not be exported, reexported, or transferred (in country) to any foreign country, or foreign entity, by any means, except in accordance with the requirements of such regulations.

Patents

EPC Corporation and EPC Space hold numerous worldwide patents. Any that apply to the product(s) listed in this document are identified by markings on the product(s) or on internal components of the product(s) in accordance with local patent laws.

eGaN® is a registered trademark of Efficient Power Conversion Corporation, Inc. Data and specification subject to change without notice.

Revisions

Datasheet Revision	Product Status
REV Q1	Characterization and Qualification
Preliminary	Production Released

Information subject to change without notice.

Revised May, 2023